

# Best In Class Finishing Solutions



## Thermal Laminators

45" & 65" Laminators with dual thermal rollers (hot/cold) allows for: Encapsulation, Lamination, Mounting & More

1-800-397-1025 | [RoyalSovereignGraphics.com](http://RoyalSovereignGraphics.com) | [graphics@royalsovereign.com](mailto:graphics@royalsovereign.com) | 2 Volvo Drive Rockleigh NJ 07467

### HIGHLIGHTS

#### **Maximize Impact**

High quality motors provide high lamination speeds resulting in faster finishing

#### **Easy To Run**

Convenient idle bars, simple one touch digital controls & quick notch adjustments

#### **Superior Service & Minimal Maintenance**

Resulting in lasting quality you can rely on

Ideal for Sign & Print businesses, Transportation & Traffic, schools, offices and more!

# Thermal Laminators



## RSH-1151 - 45" Thermal Laminator

Independently control thermal rollers will enable users the flexibility to regulate temperature based on production needs

- Maximum substrate thickness 5/8"
- Durable motor reaching up to 13 ft./min.
- Finger guard & plexi-glass cover for user safety
- Release liner take up for pressure sensitive film



## RSH-1651 - 65" Thermal Laminator

Program up to 9 different speed & temperature settings for optimal lamination and encapsulation

- Quick notch gap adjustment up to 5/8"
- Foot pedal cross cutter & rear facing remote standard
- Lamination speeds up to 13 ft./min. (cold) & 9 ft./min. (hot)
- Add a front feeder & rear rewinder for roll-to-roll lamination

Model	RSH-1151	RSH-1651
Width	45"	65"
Speed	13 ft./min. (Cold) / 9 ft./min (Hot)	13 ft./min. (Cold) / 9 ft./min (Hot)
Heat Assist	Yes	Yes
Encapsulation	Yes	Yes
Maximum Temperature	320°F	302°F
Film Thickness	1 mil - 10 mil	1 mil - 10 mil
Mounting	Up To 5/8" (16mm)	Up To 5/8" (16mm)
Dimensions (WxHxD)	66" x 36" x 58"	86" x 36" x 58"
1 Year Warranty	✓	✓