TITAN[®] 200BC with manual backgauge TITAN[®] 200



ASSURANCE YOU MADE THE RIGHT DECISION

6

TITAN[®] 200 & 200BC

Capitalizing on Challenge's time-proven expertise in manufacturing paper cutters, the TITAN[®] 200BC and 200 are engineered and manufactured to the highest of safety standards available.





200BC with manual backgauge

FEATURES AND BENEFITS

- 20" Cutting Width 3-1/4" clamp opening
- Hydraulic Cutting & Clamping
- Adjustable Clamp Pressure
- Cutting Area Protection Plexiglas safety shield
- Plexiglas Rear Table Safety Cover
- Two-Hand Cut Buttons
- Light Line Cut Position Indicator
- Manually Controlled Backgauge with Lock
- Energy Efficient Motor runs only when cutting
- Heavy Duty Casters For Portability
- Rugged Steel & Cast Iron Construction
- 12" x 19"/ 30.5 cm x 48 cm Side tables (optional)

SPECIFICATIONS

- Cutting Width: 20"/50.8 cm
- Clamp Opening: without false clamp plate 3-1/4"/8.3 cm with false clamp plate 3"/7.6 cm
- Minimum Cut: without false clamp plate: 1/2"/13mm with false clamp plate: 1-7/8" /48mm
- Maximum Cut Depth: 20"/50.8 cm
- Table Space In Front of Knife: 16"/40.6 cm
- Table Space Behind Knife: 20"/50.8 cm
- Table Height: 36″/91.4 cm
- Overall Height: 53"/135 cm
- Overall Width: 36"/91.4 cm
- Overall Length: 50-7/8"/129.3 cm
- Will Pass Through Opening: minimum required 36-1/4"/92.1 cm table, treadle & front shield off 29"/73.7 cm
- Net Weight: 755 lbs /343 kg
- Shipping Weight (approximate): 980 lbs/444 kg

ELECTRICAL (). (). CE

- 3/4 HP, Single-Phase, 60 Hz, 120 Volts, AC, 12 Amps.
- Power cord included
- Service Size 15 Amps
- Requires receptacle type: NEMA 5-15R



FEATURES AND BENEFITS

- 20" Cutting Width 3-1/4" clamp opening
- Hydraulic Cutting & Clamping
- Adjustable Clamp Pressure
- LED Line Light Cut Position Indicator
- Cutting Area Protection Plexiglas safety shield
- Plexiglas Rear Table Safety Cover
- Two-Hand Cut Buttons
- Programmable Controlled Backgauge
- Energy Efficient Motor runs only when cutting
- Heavy Duty Casters For Portability
- Rugged Steel & Cast Iron Construction
- 12" x 19"/ 30.5 cm x 48 cm Side Tables (optional)
- Optional Challenge Exclusive Ergo-Touch Cut Buttons

SPECIFICATIONS

- Cutting Width: 20″/50.8 cm
- Clamp Opening: without false clamp plate 3-1/4"/8.3 cm with false clamp plate 3"/7.6 cm
- Minimum Cut: without false clamp plate: 1/2"/13mm with false clamp plate: 1-7/8" /48mm
- Maximum Cut Depth: 20"/50.8 cm
- Table Space In Front of Knife: 15-1/4"/39 cm
- Table Space Behind Knife: 20"/50.8 cm
- Table Height: 36"/91.4 cm
- Overall Height: 53"/134.6 cm
- Overall Width: 36"/91.4 cm
- Overall Length: 49-5/8"/126 cmWill Pass Through Opening:
- minimum required 36-1/4"/92.1 cm table, treadle & front shield off 29"/73.7 cm
- Net Weight: 800 lbs /363 kg
- Shipping Weight (approximate): 980 lbs/444 kg

ELECTRICAL (1). (1) CE

- 1-1/2 HP, Single-Phase, 60 Hz, 230 Volts, AC, 12 Amps.
- Power cord included
- Service Size 15 Amps
- Requires receptacle type: NEMA 6-15R