→ 2503 CENTRALIZED OFFICE SHREDDER

"SPS" (Safety Protection System) package: electronically controlled, transparent safety shield in the feed opening; "Easy Switch" control element uses color codes and back-lit symbols to indicate operational status; automatic reverse and power cut-off in case of paper jam; automatic power cut-off when shred bag is full or when cabinet door is opened; double protection against overheating automatic start and stop controlled by photo cell | wide, 10 ¼" feed opening | high quality, hardened steel cutting shafts take staples, paper clips, and credit cards (strip-cut model takes CDs) | lifetime warranty on the cutting shafts | quiet and powerful single phase motor | durable gears enclosed in dust-proof housing | high quality wooden cabinet mounted on casters | pull-out bag frame for disposable shred bags | 26 gallon bin capacity

Dimensions (D x W x H): 14 ³/₄ x 19 ³/₄ x 34 ¹/₄ inches, Shipping weight: 92 lbs. (dimensional).



Oversized, multifunction control element uses integrated optics to indicate operational status.

ELECTRONIC SAFETY SHIELD



Safety shield in the feed opening allows safe, efficient shredding of CDs (strip-cut only).

WARR

AND	Str Shr Shr Shr Sec Sec Sec Sec	eet capacity curity level	3/16" (4 mm) 19-21* 2 10 ¼"
	Par Shi See Fee	eet capacity curity level	3/16" x 1 ½" (4 x 40 mm) 12-14* 3 10 ¼"
	Pai Shi Sei Fee	eet capacity curity level ed opening	3/32" x 5/8" (2 x 15 mm) 8-10* 4 10 ¼"
	* m	ax. horsepower ay vary due to vari nd power supply	

All technical data is approximate and subject to change. © MBM Corporation, 2/2008.